

LIFTING TECHNOLOGY **MOBILE COLUMN** LIFT

RGE TS VP 451133





RGE TS VP 451133

The mobile wheel engaging COLUMNLIFT RGE TS, with two crosspieces with adapter kit, is specifically for the lifting of tractors (equipped with corresponding C-rail), and lifts up to 7.5 t per column. Streamline column design offers a good overview when manoeuvring. The low-maintenance, electro-mechanical drive system ensures extremely smooth running while the excellent mechanical rigidity of the columns guarantees safety and the ability to function in any condition. A high-quality worm gear motor enables precision height positioning without overrun. Column communication is via connecting cable, the power supply via mains power.

PRODUCT DETAILS/ACCESSORIES

- Very smooth running due to electro-mechanical drive system
- High efficiency thanks to smooth-running, low-maintenance hall screw
- 5-year warrantee for entire spindle drive
- · Excellent lifting column mechanical rigidity guarantees safety and function under any conditions
- Specially for holding tractors with two crosspieces with adapter kit (can only be used for tractors with corresponding C-rail)
- · Precision-height positioning without overrun thanks to highquality worm gear motor
- Lifting carriages with fixed holder
- Overhead drive unit creates even more space in the work area
- Workshop-robust and splash-proof control unit
- Wear-free and easy-to-use membrane keypad
- Flexible column positioning thanks to excess-length connection cables, guaranteeing suitability across all vehicle categories
- User convenience with panel operator controls on each individual column
- High level of flexibility in use due to different operating modes
- Group and individual column operating modes enable quick

- and easy replacement of wheel and axle suspensions
- Microprocessor control and CAN bus-supported monitoring of movement synchronisation and all safety functions
- Utmost safety thanks to mechanically independent locking device
- Simple emergency lowering for power failure included as
- · System can easily be expanded with up to six columns
- Streamline COLUMNLIFT design aids manoeuvrability specifically in workstations with restricted space
- High-quality powder coating:
 - Window Grey, RAL 7040 (Columns)
 - Anthracite, Grey RAL 7016 (Lifting carriages)

Scope of delivery:

- 2 individual mobile columns
- 1 connecting cable (10m) with plug and socket
- 1 mechanical dolly, repositionable
- 2 crosspieces with adapter kit

TECHNICAL DATA

Load capacity CE per column	7500 kg
Drive power per column	1.5 kW
Weight per column	452 kg
Lifting distance	1750 mm
Raising/lowering time	113 s
Supply voltage	3/N/PE 400 V 50 Hz
Protection rating	IP 54

ACCESSORIES

VZ 971260 Single RGE Post (MAHA), 7500 kg lifting capacity incl. connection cable & plug

Remote Control TCNA 10-2 for RGF Un/Down V7 971182

with emergency stop switch

VZ 971179 Removable Mechanical Dolly, MODEL: MFR-2 Hydraulic Pallet-Type Fixed Dolly, screwed onto post MODEL: MFP

Technical Datasheet / 02/02/2023







LIFTING TECHNOLOGY MOBILE COLUMN LIFT

RGE TS VP 451133



VZ 971164	Support Stand AB 6-07, lifting capacity 7500 kg, adjustment range 470 - 795 mm (each)
VZ 971165	Support Stand AB 6-12, lifting capacity 7500 kg, adjustment range 875 - 1395 mm, mobile
VZ 971166	Support Stand AB 6-20, lifting capacity 7500 kg, adjustment range 1200-1965 mm, mobile
VZ 971168	Screw Adjustment SP 75 for AB 6-07/12/20 Support Stands

	VZ 990430	Linking cable 15 m -Extra charge per cable
	VZ 990457	Linking cable 20 m -Extra charge per cable
SUPPLEMENTARY CHARGES		
	VT 998032	Transportkosten 2 Einzelsäulen inkl. Verpackung
	VT 995698	Transportkosten 4 Einzelsäulen inkl. Verpackung
	VT 995699	Transportkosten 6 Einzelsäulen inkl. Verpackung
	VM 996077	Installation costs for mobile column lifts

